March 2017

www.solidsandbulk.co.uk

S&BH

SOLIDS&BULKHANDLING

Promoting excellence in the bulk handling industry

HEALTH & SAFETY P10

PHARMACEUTICALS P20

QUARRYING P32

MIXERS & BLENDERS P36

WEIGHING P38

DMN WESTINGHOUSE

The Pressure is On!

UP TO 3.5 BAR G

COMPONENTS FOR BULK SOLIDS HANDLING

www.dmnwestinghouse.uk

MIXER KEEPS TURNING

Rotary batch mixer from **Munson Machinery** blends wood powders for plywood adhesives

Operators at Willamette Valley Co. say the 4 cu m (3962 l) Rotary Batch Mixer delivers uniform blends in high volumes that customers demand.

To blend raw material for plywood adhesives at higher rates with greater uniformity, the Willamette Valley Company replaced a Ribbon Blender that agitates material, with a Rotary Batch Mixer that tumbles it.

The company, also known as Wilvaco, the global forest products corporation, mixes fine mesh bark powder from the Western Red Alder tree, along with other wood material, to produce dry blends that it ships to customers who formulate plywood adhesives.

Examples of the products blended include Modal SPR-Dark and Modal SPR-Lite, both bulking agents for plywood glue mixes.

NEED FOR QUALITY & HIGH THROUGHPUT

"We wanted pure blending in high volume," says Don Coleman, plant manager. "Our glue customers are very particular when it comes to their ingredients, so consistent quality is important. The ribbon blender did not mix materials thoroughly enough," he says. "The material, which customers mix in vats in their own formulations, could clog filters and shut down lines if not properly blended."

The Munson model 700-TH-140-MS at Willamette Valley blends uniformly in about four minutes, with throughput of 2721 kg per batch. Capacity of the previous ribbon blender was one third of that amount, and was being outpaced by demand.

PREVENT SEGREGATION

Coleman says the mixer's ability to continue rotating during loading and discharging prevents segregation of materials of varying densities, yielding a homogenous blend. Importantly, Willamette Valley is blending wood powder having particle sizes as small as 74 microns--finer than baking flour--without densification, Coleman says.

The constant rotation also means energy consumption remains stable and relatively low, especially when making multiple batches of one blend. The "soft start" of the motor and slow mixing speed further increase energy saving, Coleman adds.

He learned about the Rotary Batch Mixer from the plant manager at Idaho Milling and Grain, a Wilvaco company in Malad, Idaho, that blends wheat flour for glue extenders. Coleman wanted to replace the ribbon blender with a faster, higher throughput machine and his colleague, citing Idaho Milling's good experience, recommended the Rotary Batch Mixer. Given the mixer's high output, uniform blend quality and short cycle times, Willamette Valley made the investment.

From the mixer discharge the blend is pneumatically transferred to the bag filling equipment. ▶

Plywood adhesive blend consists of fine mesh bark powder from the Western Red Alder tree, along with other wood material. ◀

FEEDING THE MIXER

When tree bark—or "hog fuel" as the industry calls it—is delivered to the Willamette Valley plant, operators run it through a 3600 RPM grinder for cleaning and size reduction. The moisture content of the bark is 45 to 60%, so the powder is transported to a dryer, which reduces moisture to 6 or 7%. The bark powder is loaded into a distribution bin and conveyed to one of three PLC-controlled hoppers supplying the mixer.

Each hopper has capacity of 1362 kg and is mounted on load cells. A rotary air lock at each hopper outlet discharges material into the mixer's inlet chute. Coleman says an operator selects a recipe on the computer and pushes a "go" button, causing material to discharge from the feed hoppers. A PLC receives weight loss information from load cells and automatically stops the rotary valves once an accurate batch weight has been discharged.

As the drum rotates, proprietary mixing flights lift, cut, fold and tumble the material, achieving complete blend uniformity in one to three minutes.

The internal flights also serve to elevate the material for discharge through a pneumatically actuated plug gate valve, leaving no residual other than dust. Coleman says, "Some fine dust may be left on the flights, but this can be vacuumed away when the machine shuts down for material changeover." A side access door provides access to all interior surfaces for cleaning and inspection.

From the mixer discharge, a pneumatic conveyor transports blends 4.3 m vertically to an overhead weigh hopper equipped with load cells and a rotary valve that allows filling of 23 kg paper sacks or 1362 kg bulk bags under PLC control.

Coleman says 21,792 kg of material can be blended in eight hours. "We could do more, but we continually test batch samples and double check our products to ensure consistent quality." ■

www.munsonmachinery.com

CONVEYING HEADACHES?
Relax, we've got it covered

The Tube Chain Conveyor

For many years, conveying engineers felt something was missing. Something was needed to create order out of chaos. They couldn't relax until it was found. Then a clever idea came along. Ever since, the possibilities for reliable, smooth, energy efficient conveying have been endless! Hot or cold, dry or damp, benign, caustic, greasy or abrasive. It starts fully loaded or empty. It is the solution to their conveying worries. They can at last relax. This fantastic solution has a name:

Schrage® CONVEYING SYSTEMS

Exclusively available in the UK from Renby Limited

RENBY

CONTACT US NOW FOR A GREAT CONVEYING SOLUTION

www.renby.co.uk +44(0)1829 740913 info@renby.co.uk

POWDERS | GRANULES | PASTES | BATCH | CONTINUOUS

Boone Mixers
Optimum Mixing

Powders or Pastes
Sizes from 2 to 25,000 litres
Versatile Mixing Machines

- **Advanced Plough / Delta Blade**: Agglomerates to Paste
- **Spiral Blade**: Cake Mixes to Mastic
- **Rotary Drum**: Rice Flakes to Carpet Fibres

- Complete mixing plant design to commissioning
- Test mixers available for production development
- Production scale machines for short or long term hire

T: +44 (0)1260 272894
www.jrboone.com
e: sales@jrboone.com

JB

MIXING SOLUTIONS WORLDWIDE